



STAMP FOIL s.p.a.

NASTRI METALLIZZATI E COLORATI PER STAMPA A CALDO

INDUSTRIA GRAFICA

SCHEDA TECNICA SERIE: LH e LH HOLO.

TIPO PRODOTTO:	- foil metallizzato e metallizzato olografico;
SETTORE DI APPLICAZIONE:	- industria grafica dell'etichetta e della cartotecnica (carta comune, carta patinata) e della piccola pelletteria;
CARATTERISTICHE PRINCIPALI:	- rilascio morbido; - buona definizione; - buona coprenza; - buono per tratti fini e medie aree di stampa; - ampia gamma di colorazioni realizzabili;
CONDIZIONI DI STAMPA:	- 90°C / 130°C per stampatrici in piano; - 130°C / 160°C per stampatrici cilindriche;
MISURE STANDARD:	- larghezza: 785 mm; - lunghezza: 122-244-305-610-3050 metri; - anima: 25-75-150 mm; - spessore: 12 my; - altre misure disponibili su richiesta;
CONSIGLI DI STAMPA:	- è necessario trovare la giusta combinazione tra temperatura, tempo di sosta e pressione per raggiungere i migliori risultati di stampa;

Si prega di notare che le superfici, gli equipaggiamenti per la stampa e le condizioni di lavoro variano da cliente a cliente. E' essenziale che gli utenti finali effettuino tutti i propri test del caso per individuare il prodotto più adatto per le proprie applicazioni.

Web site:

www.stampfoil.it

Email: info@stampfoil.it



STAMP FOIL s.p.a.

NASTRI METALLIZZATI E COLORATI PER STAMPA A CALDO

GRAPHIC INDUSTRY

TECHNICAL DATA SHEET ***SERIE: LH and LH HOLO.***

PRODUCT TYPE:	- metallized foil and metallized holographic foil;
APPLICATION FIELD:	- graphic (paper, labels and greeting cards) and small leather goods industry;
MAIN CHARACTERISTICS:	- soft release; - good definition; - good coverage; - good for fine details and medium area stamping; - wide range of colours
STAMPING CONDITIONS:	- 90°C / 130°C for vertical machines; - 130°C / 160°C for cylinder machines;
STANDARD ROLL SIZES:	- width: 785 mm - length: 122-244-305-610-3050 meters - core: 25-75-150 mm - thickness: 12 my - other sizes are available on request
STAMPING HINTS:	- it is necessary to find the best adjustment between die temperature, dwell time and pressure to reach the best stamping results

Please kindly note that substrates, stamping equipment and working conditions vary for each customer. It is essential that end users carry out their own test to identify the most suitable product for their own application.

Web site:

www.stampfoil.it

Email: info@stampfoil.it